



# YANMAR L48AE

**3.5kW (4.7hp)**  
**@ 3600r/min<sup>-1</sup>**

<b>Type</b>	Single-cylinder, vertical 4-cycle air-cooled diesel
<b>Combustion System</b>	Direct injection
<b>Displacement (cc)</b>	211
<b>Bore x Stroke (mm)</b>	70 x 55
<b>Output</b>	
<b>Engine Speed (rpm)</b>	3000 3600
<b>Maximum Output (kW)</b>	3.1 3.5
<b>Maximum Output (hp)</b>	4.2 4.7
<b>Continuous Output (kW)</b>	2.8 3.1
<b>Continuous Output (hp)</b>	3.8 4.2
<b>Power Take Off</b>	Crankshaft or camshaft (Camshaft PTO is 1/2 speed)
<b>Starting System</b>	Recoil or Recoil/Electric
<b>Fuel Tank Capacity (litres)</b>	2.5
<b>Lube Oil Capacity (litres)</b>	0.8
<b>Dimensions (inches/mm)</b>	
<b>Length</b>	13.07 / 332
<b>Width</b>	15.43 / 392
<b>Height</b>	16.38 / 416
<b>Dry Weight (Recoil)</b>	26kg / 57lbs
<b>Dry Weight (Electric)</b>	31kg / 68lbs